

SIZE EF20 · OUTPUT : 24W

Primary / Secondary Insulation $\geq 2000\text{Vac}$

Ambient temperature $< 60^{\circ}\text{C}$

Construction conforms to IEC950,IEC335,IEC61558 for reinforced insulation

Exclusively uses UL94-V0 listed materials

Dimensions and Diagram (Unit mm \pm 0.5mm):		Circuit Diagram:			
24 W	Windings				
	Output Power	Pins	Turns	Inductance (+/-15%)	Resistance max. (Ω)
	Pri.	10 to 9	87	2.5 mH	1.5
	Aux.	12 to 11	14		0.3
	S1	1 to 2	11		0.1
	S2	2 to 3	7		0.15
S3	4 to 5	31		0.7	
S4	7 to 8	26		0.5	

SIZE EFD25 · OUTPUT : 30W

Primary / Secondary Insulation $\geq 2000\text{Vac}$

Ambient temperature $< 60^{\circ}\text{C}$

Construction conforms to IEC950,IEC335,IEC61558 for reinforced insulation

Exclusively uses UL94-V0 listed materials

Dimensions and Diagram (Unit mm \pm 0.5mm):		Circuit Diagram:			
30 W	Windings				
	Output Power	Pins	Turns	Inductance (+/-15%)	Resistance max. (Ω)
	Pri.	1 to 3	141	1.0 mH	2.50
	S1	7 to 8	17		0.15
S2	11 to 12	41		0.60	